

IMOLA TIMBER FRAME PARTITION (FSPEC12) K30 Specification

MANUFACTURER

Forza Doors Limited, 24a/24c Star Road Trading Estate, Star Road, Partridge Green, Horsham, West Sussex, RH13 8RA England, UK

Telephone: +44(0)1403 711126, Fax: +44(0)1403 711229

Email: sales@forza-doors.com

DETAILED DESCRIPTION

The Imola Timber/ MDF composite frame demountable and relocatable partition system provides a comprehensive range of standard elevations comprising solid, door and single centre, single offset or double glazed modules.

Performance :

Fire resistance to BS 476-22:1987 up to FD60 for glazed, solid and door modules.

Sound insulation to BS EN ISO 10140-2-2010 : single glazed module up to 35dB(Rw); double glazed module up to 51dB(Rw); single door module up to 40dB(Rw) Solid up to 51dB(Rw).

Veneer panel surface spread of flame classification Class 1 when tested in accordance with BS476 Part 7 : 1997.

Imola complies with Structural guidelines recommended in BS5234-2 Partitions 1992 and BS6180-2011 Barriers in and about Buildings.

Doorset resistance to vertical load to BS EN 947 : 1999 : Severe Duty

Doorset resistance to soft body impact To BS EN 949:1999 : Severe Duty

Product Guidance – As Standard

Partition Height up to 3000mm. Module width up to 1200mm

Frame dimensions : non fire frame face 45mm X depth ((ma) to suite 75mm solid) 103mm ((mb) to suite 100mm solid) 128mm, ((mc) to suite 122mm solid) 150mm

Fire frame face 60mm X depth ((ma) to suite 75mm solid) 103mm

((mb) to suite 100mm solid) 128mm, ((mc) to suite 122mm solid) 150mm

IMOLA TIMBER FRAME PARTITION (FSPEC12) K30 Specification

Options

Frame finish as delivered

All commercially available timber / veneers – Clear / tinted : U/V lacquer Standard 20% gloss level / other. Stained Colour & finished with u/v Standard gloss 20% gloss level / other.

All commercially available RAL colours : high solid pigmented lacquer “paint finish” Standard gloss 20% / other.

For onsite finishing by others : Pre-cat primer unsanded for onsite denib & coat with either standard water based latex/ acrylic or oil based (alkyd) topcoat paint.

Modules – Non Fire

Glazed

Single Glazed with mullions - offset/central – Toughened glass (size limit 6mm / 8mm) / 10mm (34dBRw) / 12mm (35dBRw).

Single Glazed mullion free glass to glass –offset/central–Toughened glass 10 mm(34dBRw)/12mm(35dBRw).

Double glazed with mullions – Toughened glass 10mm & 6mm(42dBRw) / 12mm & 10mm(49dBRw).

Double glazed mullion free glass to glass – Toughened glass 12mm & 10mm (49dBRw).

Door

Standard door & frame.

Flush face door & frame.

Concealed doorframe with sequentially matched veneer panel and door.

Solid

Wrap round transition post.

Flush shadow gap.

Veneer panel (prepared for room book system).

Modules – Fire

Glazed

Single Glazed with mullions –Offset – FD30/0 GFP 12mm (2900mm x 1000mm)

/ FD30/30 GFP 16mm (2900mm x 1200mm)

Single Glazed mullion free glass to glass – offset - FD30/30 GFP20 (2900mm x 1200mm)

IMOLA TIMBER FRAME PARTITION (FSPEC12) K30 Specification

Single Glazed with mullions – Offset – FD60/0 GFP12mm (2400mm x 900mm)
FD60/30 GFP16 mm(2900mm x 1200mm) FD60/60 GFP25mm(2900mm x 1200mm)
Single Glazed mullion free glass to glass – offset - FD60/60 GFP25mm (2900mm x 1200mm)
Double glazed – Consult with Imola technical department

Door

Standard door & frame FD30 (44mm) / FD60 (54mm)

Solid - To drywall manufacturers specification

TIMBER/MDF MOISTURE CONTENT ON DELIVERY

Comply with BS EN 942:2007 service climate 12-21°C / above 21°C 12 %.

SITE CONDITIONS

Conditions for storage, handling, stacking and covering of timber/MDF framing during installation to comply with manufacturer's instructions.

Post installation temperature to be in region 12°C to 21°C and relative humidity range 40% to 60%.

INSTALLATION

Fix timber/MDF frame(s), glass panel's seals and bead in accordance with Imola Installation guides FZD5043 to FZD5048.