



# FORZA DOORS FD90 INTUMESCENT SEAL SPECIFICATION

### Intumescent Seal Specification for FCW90 Door Leaves Installed in Timber Frames

Location	Size and Position
Stiles/Frame	Forza PVC-seals 1no 20 x 4 mm seal fitted in a groove 7 mm from the pull face in the frame reveal 1no 25 x 4 mm seal fitted in a groove 33 mm from the pull face in the frame reveal
Head/Frame	Forza PVC-seals 1no 20 x 4 mm seal fitted in a groove 7 mm from the pull face in the frame reveal 1no 25 x 4 mm seal fitted in a groove 33 mm from the pull face in the frame reveal
Base/Door	Forza Palusol 1no 50 x 2 mm seal fitted centrally in the leaf edge.
Square meeting stiles	Forza PVC-seals 2no 20 x 4 mm seals; 1no fitted in each leaf edge, with one set 5 mm from the pull face and the other set 5 mm from the push face
Transom/Frame	Forza PVC-seals  1no 20 x 4 mm seal fitted in a groove 7 mm from the pull face in each side transom reveal  1no 25 x 4 mm seal fitted in a groove 33 mm from the pull face in each side transom reveal



## FORZA DOORS FD90 INTUMESCENT SEAL SPECIFICATION

#### Intumescent Seal Specification for FCW90 Door Leaves Installed in Composite Frames

Location	Size and Position
Stiles/Frame	Forza PVC-seals 1no 20 x 4 mm seal fitted in a groove 7 mm from the pull face in the frame reveal 1no 25 x 4 mm seal fitted in a groove 33 mm from the pull face in the frame reveal
Head/Frame	Forza PVC-seals 1no 20 x 4 mm seal fitted in a groove 7 mm from the pull face in the frame reveal 1no 25 x 4 mm seal fitted in a groove 33 mm from the pull face in the frame reveal
Base/Door	Forza Palusol 1no 50 x 2 mm seal fitted centrally in the leaf edge.
Square meeting stiles	Forza PVC-seals 2no 20 x 4 mm seals; 1no fitted in each leaf edge, with one set 5 mm from the pull face and the other set 5 mm from the push face
Transom/Frame	Forza PVC-seals 1no 20 x 4 mm seal fitted in a groove 7 mm from the pull face in each side transom reveal 1no 25 x 4 mm seal fitted in a groove 33 mm from the pull face in each side transom reveal



## FORZA DOORS FD90 INTUMESCENT SEAL SPECIFICATION

#### Intumescent Seal Specification for FCH90 Door Leaves Installed in Steel Frames

Location	Size and Position
Stiles/Frame	1no 60 x 1 mm surface fitted centrally in the frame reveal
Head/Frame	1no 60 x 1 mm surface fitted centrally in the frame reveal
Base/Door	1no 50 x 1 mm intumescent seal fitted centrally in the bottom edge of the leaf